



Pipe Lifting Clamp TPH/TPH-HD

Product information

Heavy duty clamp with high pressure resistant plastic for horizontal pipe lifting. Clamp for horizontal lifting and transporting of steel and concrete pipes without damaging the product.

Model THP: Standard clamp

Model THP-HD: special for extreme heavy duty lifting situations

Features:

- TPH Jaw is covered with a special high quality pressure resistant plastic.
- TPH-HD Jaw is covered with special high quality extreme high pressure resistant plastic.
- Maintenance-friendly clamps, plastic pressure resistant cover is easy to change.
- TPH-HD has special handle for easy handling.
- Compact design and high lifting capacity.
- Lightweight design for easy handling.
- Tough quality heavy duty body.

Marking: According to standard, CE-marked, Type, serial number, WLL, Jaw opening

Temperature range: TPH: - 40°C to + 50°C. / TPH-HD - 30°C to + 80°C.

Standard: EN 13155

Note: Must always be used in pairs

Part code	Code	WLL ton	Jaw width mm	V mm mm	S mm mm	Wmm mm	U mm mm	T mm mm	X mm mm	Ymm mm	Weight kg	Delivery time
502100150400740	1.5 TPH	1.5	40	120	70	50	185	16	41	25	2	7
502100300400740	3 TPH	3	40	120	70	50	185	16	41	25	2	7
502100400500740	4 TPH	4	50	140	70	58	204	26	41	25	3	7
502100600500740	6 TPH	6	50	140	70	58	204	26	41	25	3	7
502100800700740	8 TPH	8	70	140	70	58	224	26	45	25	3.4	7
502101000700740	10TPH	10	70	140	70	58	224	26	85	45	5	7
502101200700740	12TPH	12	70	140	70	58	224	26	85	45	7	7
502101500700740	15TPH	15	70	155	70	76	250	26	100	60	9	7
502102000700740	20TPH	20	70	155	70	76	250	26	100	60	9	7

Blueprint

