



Turnbuckle Hook - Hook G-6312, Green Pin®

Product information

The Green Pin® HH Turnbuckle is a turnbuckle with hook-hook end-fittings, generally to ASTM F1145-92. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. Galvanization of the Green Pin® HH Turnbuckle ensures its long-term durability. The turnbuckle is available in a range with a diameter thread of 3/8" (take up of 6") up to 1" (take up of 24").

Certification on request: 2.1, 2.2, 3.1, MTCa

Standard: Generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b.

Material: Drop forged high tensile steel SAE 1035 or 1045.

Marking: CE-marked

Temperature range: -20°C up to +200°C

Finish: Hot dip galvanized.

Safety factor: 5:1

Part code	WLL ton	Thread	Take up inch	a" mm	b mm mm	c mm	dmm mm	e mm mm	f mm mm	g mm mm	Weight kg	Delivery time
422100540310	0.54	3/8	6	3/8	278	415	13	16	15	42	0.53	7
422100680310	0.68	1/2	12	1/2	456	739	13	19	16	47	1.34	7
422100100310	1	1/2	6	1/2	305	434	16	22	16	48	0.93	7
422100100315	1	1/2	9	1/2	380	587	16	22	16	47	1.16	7
422100140310	1.36	3/4	9	3/4	468	664	20	27	24	78	2.49	7
422100160310	1.59	5/8	6	5/8	356	479	16	23	21	67	1.4	7
422100160316	1.59	5/8	12	5/8	507	784	16	23	21	66	1.79	7
422100160315	1.59	5/8	9	5/8	431	632	20	24	21	66	1.96	7
422100230315	2.27	1	18	1	778	1,191	26	35	31	106	6.5	7
422100230316	2.27	1	24	1	928	1,495	26	35	31	105	8.13	7
422100240310	2.36	3/4	6	3/4	393	511	22	27	24	78	2.04	7
422100240315	2.36	3/4	12	3/4	544	816	22	27	24	78	3.27	7
422100450310	4.54	1	6	1	479	586	26	35	31	109	4.23	7
422100450315	4.54	1	12	1	625	886	26	35	31	106	6.64	7

Blueprint

