

Turnbuckles Eye - Jaw Green Pin® G-6315

Product information



The Green Pin® EJ Turnbuckle is a turnbuckle with eye-jaw end-fittings. The jaw is fitted with a safety bolt for sizes with a diameter thread up to 5/8" and fitted with a cotter pin for sizes with a diameter thread 3/4" and up. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. Galvanization of the Green Pin® EJ Turnbuckle ensures its long-term durability. The turnbuckle is available in a range with a diameter thread 3/8" (take up of 6") up to 2 3/4" (take up of 24").

Are equipped with pins and cotters.

Certification on request: 2.1, 2.2, 3.1, MTCa

Standard: generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b

... [Read more](#)

Material: drop forged high tensile steel SAE 1035 or 1045

Marking: CE-marked

Temperature range: -20°C up to +200°C


Finish: hot dipped galvanized

Note: jaw ends up to and including 5/8" are fitted with bolts and nuts, sizes 3/4" and up

Safety factor: 5:1

Turnbuckles Eye - Jaw Green Pin® G-6315

Blueprint



Technical data

Part code	WLL ton	Thread Inch	Take up inch	a " mm	b mm mm	c mm	dmm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	j mm mm	k mm mm	l mm mm	Weight kg
422100540290	0.54	3/8	6	3/8	283	418	12	21	8	9	21	10	13	29	49	0.52
422100100290	1	1/2	6	1/2	315	446	16	26	10	11	25	12	18	36	58	0.88
422100100295	1	1/2	9	1/2	390	598	16	26	10	11	25	12	18	36	57	1.13
422100100296	1	1/2	12	1/2	466	751	16	26	10	11	25	12	18	36	57	1.37
422100160290	1.59	5/8	6	5/8	363	486	18	32	13	14	33	14	21	45	79	1.55
422100160295	1.59	5/8	9	5/8	438	639	18	32	13	14	33	14	21	45	78	1.84
422100160296	1.59	5/8	12	5/8	514	790	18	32	13	14	33	14	21	45	78	2.17
422100240290	2.36	3/4	6	3/4	391	510	24	38	16	16	41	17	26	54	89	2.28
422100240295	2.36	3/4	9	3/4	467	663	24	38	16	16	41	17	26	54	89	2.82
422100240296	2.36	3/4	12	3/4	542	815	24	38	16	16	41	17	26	54	88	2.95
422100240297	2.36	3/4	18	3/4	694	1,120	24	38	16	16	41	17	26	54	89	3.3
422100330290	3.27	7/8	12	7/8	583	848	27	42	19	19	48	20	32	61	101	4.35
422100330295	3.27	7/8	18	7/8	735	1,153	27	42	19	19	48	20	32	61	101	5.46
422100450297	4.5	1	24	1	928	1,494	31	50	22	20	54	24	37	76	116	8.35
422100450296	4.54	1	6	1	473	579	31	50	22	20	54	24	37	76	118	4.66
422100450290	4.54	1	12	1	624	884	31	50	22	20	54	24	37	76	117	5.94
422100450295	4.54	1	18	1	776	1,190	31	50	22	20	54	24	37	76	117	7.98
422100690290	6.9	1 1/4	12	1 1/4	677	950	44	71	29	26	68	29	47	91	145	10.4
422100690295	6.9	1 1/4	18	1 1/4	833	1,258	44	71	29	26	68	29	47	91	144	11
422100690296	6.9	1 1/4	24	1 1/4	989	1,566	44	71	29	26	68	29	47	91	144	12.9
422100970290	9.71	1 1/2	12	1 1/2	716	983	52	71	35	28	80	32	55	106	156	13.1
422100970295	9.71	1 1/2	18	1 1/2	871	1,290	52	71	35	28	80	32	55	106	160	14.7

Turnbuckles Eye - Jaw Green Pin® G-6315

Technical data

Part code	WLL ton	Thread Inch	Take up inch	a " mm	b mm mm	c mm	d mm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	j mm mm	k mm mm	l mm mm	Weight kg
422100970296	9.71	1 1/2	24	1 1/2	1,023	1,594	52	71	35	28	80	32	55	106	158	17.8
422101270290	12.7	1 3/4	18	1 3/4	979	1,356	60	86	41	33	90	38	61	120	197	22.3
422101270295	12.7	1 3/4	24	1 3/4	1,130	1,662	60	86	41	33	90	38	61	120	196	27.5
422101680290	16.8	2	24	2	1,208	1,728	63	93	51	40	107	46	69	147	230	42.9
422102720290	27.2	2 1/2	24	2 1/2	1,343	1,899	75	114	57	41	143	51	80	165	274	68
422103400290	34	2 3/4	24	2 3/4	1,399	1,953	90	110	70	41	158	57	84	178	284	91