

Clevis Masterlink X-059

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL
... [Read more](#)

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.


Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Clevis Masterlink X-059

Blueprint



Technical data

| Part code | Chain diameter mm | WLL ton | EWL mm | A mm | G mm | H mm | K mm | L mm | T mm | Weight kg |
|--------------|-------------------|---------|--------|------|------|------|------|------|------|-----------|
| 402100250510 | 7-8 | 2.5 | 99 | 10 | 65 | 15 | 103 | 83 | 19 | 0.4 |
| 402100400510 | 10 | 4 | 125 | 11 | 96 | 19 | 133 | 108 | 19 | 0.8 |
| 402100670510 | 13 | 6.7 | 168 | 14 | 108 | 22 | 168 | 136 | 25 | 1.5 |
| 402101000510 | 16 | 10 | 198 | 18 | 124 | 26 | 203 | 165 | 27 | 2.4 |