



## Clevis Foundry Hook X-046 Grade 10

### Product information

At least 25% greater WLL than traditional Grade 8 products.

Testing according to DIN PAS 1061 and ASTM A952/A 952M.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Tempering temperature minimum 400°C.

Designed for the assembly of chain slings where wide throat openings are necessary.

**Material:** Quenched and tempered alloy steel.

**Marking:** According to standard, Size, grade, manufacturer ID, traceability.

**Temperature range:** -40°C up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-1

**Warning:** Before using the hook, check whether hooks without safety latches are allowed to be used for the particular application.

**Safety factor:** 4:1

**Grade:** 10

| Part Code    | WLL<br>ton | For chain Grade 10 Ø<br>mm | A<br>mm | H<br>mm | K<br>mm | P<br>mm | T<br>mm | Weight<br>kg | Delivery time |
|--------------|------------|----------------------------|---------|---------|---------|---------|---------|--------------|---------------|
| 402300250770 | 2.5        | 7,8                        | 9       | 27      | 133     | 62      | 19      | 0.95         | 7             |
| 402300400770 | 4          | 10                         | 11      | 32      | 163     | 74      | 23      | 1.8          | 7             |
| 402300670770 | 6.7        | 13                         | 14      | 39      | 200     | 88      | 32      | 3.6          | 7             |
| 402301000770 | 10         | 16                         | 18      | 47      | 239     | 98      | 41      | 6.4          | 7             |
| 402301600770 | 16         | 20                         | 21      | 62      | 305     | 113     | 46      | 11.2         | 7             |

## Blueprint

