

## **Beam Clamp Powertex PBC-S1**

## **Product information**





Powertex Beam Clamp PBC-S1 is durable and easy to install on different beam types. The beam clamp is designed to provide quick rigging and hoisting points for a great variety of applications.

## Features:

- Safe All Powertex Beam Clamps are proof load tested 2 x WLL
- Compact, lightweight construction
- · Low headroom design
- Durable all steel construction with powder coated finish and black plated spindle and grip
- RFID equipped (chip) for easy service and inspection
- QR code for on-site access to Multilanguage user manuals
- Test certificate and Declaration of Conformity enclosed with each beam clamp
- Can be turned into Blackline version by adhering the included grey label over the shiny nameplate

Blackline products are suitable for use in theatres and the entertainment industry.

Marking: According to standard, CE-marked, Powertex, Model, WLL, Serial number, QR code

Temperature range: -10°C up to +50°C.

Finish: Black powder coating.

Standard: EN 13155

Safety factor: 4:1.

| Part code       | Code    | WLL<br>ton | Beam width<br>mm | A max<br>mm | B min<br>mm | B max<br>mm | C mm | D<br>mm | E<br>mm | H<br>mm | F min<br>mm | F max<br>mm | G min<br>mm | Weight<br>kg | Delivery time |
|-----------------|---------|------------|------------------|-------------|-------------|-------------|------|---------|---------|---------|-------------|-------------|-------------|--------------|---------------|
| 502300102400040 | 1t PBC  | 1          | 80-240           | 270         | 183         | 370         | 94   | 4       | 198     | 20      | 100         | 154         | 22          | 3.5          | 3             |
| 502300202400040 | 2t PBC  | 2          | 80-240           | 270         | 183         | 370         | 102  | 6       | 198     | 20      | 100         | 154         | 22          | 4.5          | 3             |
| 502300303300040 | 3t PBC  | 3          | 90-330           | 355         | 243         | 500         | 132  | 8       | 263     | 22      | 148         | 219         | 46          | 9.5          | 3             |
| 502300503300040 | 5t PBC  | 5          | 90-330           | 355         | 243         | 500         | 142  | 10      | 263     | 28      | 148         | 219         | 43          | 11           | 7             |
| 502301003500040 | 10t PBC | 10         | 90-350           | 364         | 269         | 521         | 180  | 12      | 285     | 38      | 165         | 239         | 51          | 16           | 7             |

## Blueprint

