



General use



## Steel Wire Rope ROPETEX S49

### Product information

**ROPETEX**



SZ

G



ROPETEX S49 is a wire rope for general purposes like hanging signs, control and signaling devices, but not for lifting. It's most used in small diameters up to 6 mm. ROPETEX S49 is equipped with a Steel Core (WSC).

ROPETEX S42 is the same rope but has a Fibre Core (FC) and is therefore more flexible.

**Rope construction:** 6x7-WSC (7x7)

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C, for operating temperatures between 100°C and 200°C reduce MBF by minus 10 %.

**Standard:** EN 12385-4

**Warning:** Not to be used for lifting purposes

**Fill factor:** 0,55

Part code	Rope diameter mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay	Min. breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m	Delivery time
101100104270040	1	1,960	Galvanized	sZ	0.76	0.43	Dry	0.38	3
101100154270040	1.5	1,960	Galvanized	sZ	1.71	0.97	Dry	0.86	3
101100204270040	2	1,960	Galvanized	sZ	3.04	1.73	Dry	1.54	7
101100304270040	3	1,960	Galvanized	sZ	6.84	3.89	Dry	3.46	7
101100404270040	4	1,960	Galvanized	sZ	12.2	6.91	Dry	6.14	7
101100604270040	6	1,960	Galvanized	sZ	27.4	15.6	Dry	14	7