



General use



Steel Wire Rope ROPETEX S42 PVC

Product information

ROPETEX



SZ

G



ROPETEX S42 is a galvanized rope equipped with a Fibre Core (FC) and has a PVC coating. It can be used for various applications such as locking rope, signaling devices, etc but not for lifting. It's most used in small diameters up to 8 mm.

Available with transparent, matt black or a matt Red (RAL 3020) PVC coating.

The PVC coating is UV stabilized which makes it suitable for longterm outdoor use and it is fully compliant with REACH Directive 1907/2006.

Rope construction: 6x7 FC

Marking: According to standard

Temperature range: -30°C up to +70°C

Standard: EN 12385-4

except from coating

Warning: Not to be used for lifting purposes

Fill factor: 0,47

Part code	Rope diameter mm	Inner diameter mm	Colour	Tensile strength N/mm ²	Min. breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m	Delivery time
105130030020010	3	2	transparent	1,770	2.35	3.32	Dry	2.1	7
105130040020010	4	2	transparent	1,770	2.35	5.9	Dry	2.7	3
105130040030010	4	3	transparent	1,770	5.29	5.9	Dry	4.1	3
105130040030014	4	3	Black	1,770	5.29	5.9	Dry	4.1	7
105130040030012	4	3	Red	1,770	5.29	5.9	Dry	4.1	7
105130050030010	5	3	transparent	1,770	5.29	9.23	Dry	5.3	3
105130050030012	5	3	Red	1,770	5.29	9.23	Dry	5.3	7
105130050040012	5	4	Red	1,770	9.4	9.23	Dry	6.9	7
105130060040010	6	4	transparent	1,770	9.4	13.3	Dry	8.3	3
105130060050010	6	5	transparent	1,770	14.7	13.3	Dry	10	7
105130070050010	7	5	transparent	1,770	14.7	18.1	Dry	12.1	7
105130080060010	8	6	transparent	1,770	21.2	23.6	Dry	15.2	7