

Direct VIP chain connection PowerPoint® WPPH-VIP



Product information

















Universal connection with many attachment options.

- ideal connection link for crossbars construction
- clear marking of the minimum WLL
- compact design

Marking: WLL

Safety factor: 4:1

Technical data

Method of lift										
Lifting from the side	Attention, when lifting point is attached to the side the max. inclination angle β can only be 25° / resp. until lifting means touches load (compare 4.2, 6)!									
Number of legs	1	1	2	2	2	2	2	3 & 4	3 & 4	3 & 4
Angle of inclination $\angle \beta$	0°	90°	0°	90°	0-45°	45-60°	unsymm.	0-45°	45-60°	unsymm.
Factor	1	1	2	2	1.4	1	1	2.1	1.5	1
Type	Max. weight of load >G< in metric tons for all PowerPoint types with different sling methods									
WPP / WPPH - ... - 0.63 t	0.63 t (1385 lbs)	0.63 t (1385 lbs)	1.26 t (2770 lbs)	1.26 t (2770 lbs)	0.88 t (1940 lbs)	0.63 t (1385 lbs)	0.63 t (1385 lbs)	1.32 t (2900 lbs)	0.95 t (2080 lbs)	0.63 t (1385 lbs)
WPP / WPPH - ... - 1.5 t	1.5 t (3300 lbs)	1.5 t (3300 lbs)	3.0 t (6600 lbs)	3.0 t (6600 lbs)	2.1 t (4620 lbs)	1.5 t (3300 lbs)	1.5 t (3300 lbs)	3.15 t (6930 lbs)	2.25 t (4950 lbs)	1.5 t (3300 lbs)
WPP / WPPH - ... - 2.5 t	2.5 t (5500 lbs)	2.5 t (5500 lbs)	5.0 t (11000 lbs)	5.0 t (11000 lbs)	3.5 t (7700 lbs)	2.5 t (5500 lbs)	2.5 t (5500 lbs)	5.25 t (11550)	3.75 t (8250 lbs)	2.5 t (5500 lbs)
WPP / WPPH - ... - 4 t	4.0 t (8800 lbs)	4.0 t (8800 lbs)	8.0 t (17600 lbs)	8.0 t (17600 lbs)	5.6 t (12320 lbs)	4.0 t (8800 lbs)	4.0 t (8800 lbs)	8.4 t (18480 lbs)	6.0 t (13200 lbs)	4.0 t (8800 lbs)
WPP / WPPH - ... - 5 t	6.7 t (15000 lbs)	5.0 t (11000 lbs)	13.4 t (30000 lbs)	10.0 t (22000 lbs)	7.0 t (15400 lbs)	5.0 t (11000 lbs)	5.0 t (11000 lbs)	10.5 t (23100 lbs)	7.5 t (16500 lbs)	5.0 t (11000 lbs)
WPP / WPPH - ... - 8 t	10.0 t (22000 lbs)	8.0 t (17600 lbs)	20.0 t (44000 lbs)	16.0 t (35200 lbs)	11.2 t (24640 lbs)	8.0 t (17600 lbs)	8.0 t (17600 lbs)	16.8 t (36960 lbs)	12.0 t (26400 lbs)	8.0 t (17600 lbs)

Blueprint

