

## Master link oversized, grade 80

---

### Product information



Extra large masterlink for chain sling assemblies.

[... Read more](#)

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, yellow

**Standard:** EN 1677-4


**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 8

## Master link oversized, grade 80

### Blueprint



### Technical data

| Part code   | WLL<br>ton | EWL<br>mm | For chain, 1-leg<br>mm | For chain, 2-leg<br>mm | A mm | B mm | D mm | Weight<br>kg |
|-------------|------------|-----------|------------------------|------------------------|------|------|------|--------------|
| 4011NOR16B7 | 3.2        | 190       | 10                     | 7/8                    | 190  | 100  | 16   | 0.86         |
| 4011NORY025 | 6.4        | 300       | 13                     | -                      | 300  | 210  | 25   | 5.53         |
| 4011NOR22B7 | 7          | 210       | 13                     | 10                     | 210  | 110  | 22   | 1.83         |
| 4011NOR28B7 | 11.5       | 270       | 16                     | 13/16                  | 270  | 140  | 28   | 3.8          |
| 4011NOR32B6 | 17         | 270       | 22                     | 20                     | 270  | 140  | 32   | 5.05         |
| 4011NOR38B7 | 19         | 400       | 22                     | 20                     | 420  | 220  | 38   | 10.78        |
| 4011NOR45B7 | 27         | 470       | 26                     | 22                     | 470  | 250  | 45   | 17.06        |
| 4011NOR38B6 | 28         | 420       | 26                     | 22                     | 270  | 140  | 38   | 7.29         |
| 4011NOR50B6 | 45         | 380       | 36                     | 32                     | 380  | 200  | 50   | 17.65        |