



Clevis Grab Hook X-042

Product information

- At least 25% greater WLL than traditional Grade 8 products.
- Testing according to DIN PAS 1061 and ASTM A952/A 952M.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Enables full WLL while in use, thanks to supporting wings which prevent chain link deformation.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL.

Material: Quenched and Tempered Alloy Steel

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Standard: EN 1677-1

Warning: Not for use with Omega Link

Safety factor: 4:1

Grade: 10

Part Code	Chain diameter mm	WLL ton	A mm	F mm	H mm	K mm	L mm	P mm	Weight kg	Delivery time
402300140810	6	1.4	7	25	18	47	79	8	0.2	7
402300250810	7-8	2.5	10	30	22	54	93	10	0.4	7
402300400810	10	4	11	41	29	77	128	13	0.8	7
402300670810	13	6.7	15	52	38	99	165	17	1.6	7
402301000810	16	10	18	57	45	114	195	21	2.7	7
402301600810	20	16	22	73	52	130	222	23	4.8	7
402301900810	22	19	24	70	56	139	247	26	6.4	7

Blueprint

