



## Welded Master Link X-0080

### Product information

- Welded Master Link designed for 1 leg chain, wire rope and webbing slings.
- At least 25% greater WLL than traditional Grade 8 products.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

**Material:** Quenched and Tempered Alloy Steel

**Marking:** According to standard, CE-marked, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL)

**Finish:** Blue Painted

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

| Part Code    | Code  | WLL<br>ton | Proof Load<br>kN | For chain gr 10 Ø 1 leg<br>mm | WLL β 0-45° | Used to single hook acc. to DIN 15401 No. | D<br>mm | A<br>mm | B<br>mm | Weight<br>kg | Delivery time |
|--------------|-------|------------|------------------|-------------------------------|-------------|---|---------|---------|---------|--------------|---------------|
| 402100670540 | ED-28 | 6.7        | 164              | 13                            | 6,7         | 25  | 28      | 340     | 180     | 4.7          | 7             |
| 402101000540 | ED-32 | 10         | 245              | 16                            | 10          | 25  | 32      | 340     | 180     | 6.2          | 7             |
| 402101900540 | ED-40 | 19         | 466              | 20,22                         | 19          | 25  | 40      | 340     | 180     | 10           | 7             |

## Blueprint

