



Clevis Sling Hook with Forged Safety Latch HKS/SUN

Product information

General: General purpose hook.

Marking: According to standard

Temperature range: -40 °C up to 200 °C

Standard: EN 1677-3

Safety factor: 4:1

Grade: 12

| Part code | Code | Chain diameter mm | WLL ton | Chain Ø inch | e mm | h mm | a mm | b mm | d mm | g1 mm | Weight kg | Delivery time |
|--------------|------------|----------------------|------------|-----------------|---------|---------|---------|---------|---------|----------|--------------|---------------|
| 403300240070 | HKS/SUN 7 | 7 | 2.36 | 9/32 | 93 | 27 | 21 | 89 | 9,5 | 26 | 0.67 | 7 |
| 403300300070 | HKS/SUN 8 | 8 | 3 | 5/16 | 92 | 27 | 21 | 89 | 11 | 26 | 0.67 | 7 |
| 403300500070 | HKS/SUN 10 | 10 | 5 | 3/8 | 108 | 33 | 25 | 110 | 14 | 31 | 1.23 | 7 |
| 403300800070 | HKS/SUN 13 | 13 | 8 | 1/2 | 130 | 41 | 34 | 132 | 17,5 | 38 | 2.42 | 7 |
| 403301220070 | HKS/SUN 16 | 16 | 12.2 | 5/8 | 158 | 49 | 37 | 160 | 21 | 45 | 4.22 | 7 |

Blueprint

