

Stainless steel clevis sling hooks with latch



Product information

Clevis sling hook with latch. Hook is equipped with spring loaded safety latch. Attachment directly to the chain with clevis link.

Material: AISI 316

Marking: CE-marked

Temperature range: -40 - (+)400°C

Warning: Not to be heat-treated

Safety factor: 4:1

| Part code | WLL ton | For chain Ø mm | a mm | b mm | c mm | d mm | e mm | f mm | g mm | h mm | i mm | Weight kg | Delivery time |
|--------------|---------|----------------|------|------|------|------|------|------|------|------|------|-----------|---------------|
| 400300070040 | 0.7 | 6 | 76 | 7 | 25 | 15 | 19 | 27 | 73 | 109 | 8 | 0.29 | 7 |
| 400300120040 | 1.2 | 8 | 95 | 9 | 28 | 20 | 22 | 32 | 85 | 133 | 9 | 0.55 | 7 |
| 400300160040 | 1.6 | 10 | 113 | 11 | 28 | 24 | 28 | 41 | 106 | 164 | 13 | 0.97 | 7 |
| 400300270040 | 2.7 | 13 | 138 | 15 | 38 | 32 | 40 | 52 | 133 | 208 | 16 | 1.86 | 7 |

Blueprint

