Lifting Solutions Group
Axel Johnson International

Spur Gear Hand Winch TL1500 SST Stainless

Product information



This spur gear winch is fast, easy and can be mounted on both walls and floors. The free spool option is therefore also available for this winch.

- robust and safe lifting and pulling winch
- protection classification IP54
- load pressure brake with double ratchet system for safe stable hold of the load in any position
- cable outlet upwards, downwards or at the left
- closed gearbox to protect against environmental influence
- adjustable crank
- suitable for wall and floor mounting
- Stainless steel 304

Options:

- zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- stainless steel grade 304 (SST304)
- 2 drum compartment (2D)
- free-spooling device for pulling applications. To disengage the drum (FS)
- ATEX certified zone 2 and 22 (EX)

  CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
  CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

... *Read more*

Material: Stainless steel 304
Marking: According to standard, CE-mark
Temperature range: -20°C up to +70°C
Standard: EN 13157
Note: The cable must be ordered separately, ask for more information about our sales


Safety factor: 4:1

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Spur Gear Hand Winch TL1500 SST Stainless

Blueprint



Technical data

Part code	Code	WLL ton	Rope Ø mm	Rope capacity m	Capacity 1st layer kg	Capacity top layer kg	Weight kg
501300150001060	TL1500 SST	1.5	10	21	1,500	927	27.5

© November 2026 - All Rights Reserved