

Anchor Point ABS-Lock III-ST



Product information

Stainless steel anchor point ABS-Lock III-ST (Ø 16 mm) is a fall protection solution for steel (roofs, walls, facades and overhead installation) designed for countering or cementing-in. Inserted into a predrilled hole and countered using a nut. Incl. installation set. Protruding and non-protruding models available.

Add a supporting tube for usage as a corner or curve element in a lifeline system.

Force directions: Lateral and axial

Substructure: Steel

Attachment: Countered, screwed

Application: Flat roofs, facade/wall, overhead

Material: Stainless steel

Marking: According to standard, CE-marked, Safety Instructions, Supplier symbol, Batch Nr., Standards, Max No of simultaneous users, Serial Nr.

Standard: EN 795, CEN/TS/16415

Note: Incl. installation set

Part code	Max. number of persons	Length mm	Thread length mm	Delivery time
8415L3ST5045	3	50	45	7
8415L3ST10045	3	100	45	7
8415L3ST20045	3	200	45	7
8415L3ST30045	3	300	45	7
8415L3ST40045	3	400	45	7
8415L3ST50045	3	500	45	7
8415L3ST60045	3	600	45	7
8415L3ST045	3	-	45	7
8415L3ST0100	3	-	100	7