

Anchor Point ABS-Lock III-ST

Product information



Stainless steel anchor point ABS-Lock III-ST (Ø 16 mm) is a fall protection solution for steel (roofs, walls, facades and overhead installation) designed for countering or cementing-in. Inserted into a predrilled hole and countered using a nut. Incl. installation set. Protruding and non-protruding models available.

Add a supporting tube for usage as a corner or curve element in a lifeline system.

Force directions: Lateral and axial

Substructure: Steel

Attachment: Countered, screwed

Application: Flat roofs, facade/wall, overhead

Material: Stainless steel

Marking: According to standard, CE-marked, Safety Instructions, Supplier symbol, Batch Nr., Standards, Max No of simultaneous users, Serial Nr.

Standard: EN 795, CEN/TS/16415

Note: Incl. installation set

| Part Code | Max. number of persons | Length mm | Thread length mm | Delivery time |
|---------------|------------------------|-----------|------------------|---------------|
| 8415L3ST045 | 3 | - | 45 | 7 |
| 8415L3ST0100 | 3 | - | 100 | 7 |
| 8415L3ST5045 | 3 | 50 | 45 | 7 |
| 8415L3ST10045 | 3 | 100 | 45 | 7 |
| 8415L3ST20045 | 3 | 200 | 45 | 7 |
| 8415L3ST30045 | 3 | 300 | 45 | 7 |
| 8415L3ST40045 | 3 | 400 | 45 | 7 |
| 8415L3ST50045 | 3 | 500 | 45 | 7 |
| 8415L3ST60045 | 3 | 600 | 45 | 7 |