



## Textile lifting slings - GeoLift

### Product information

**General:** Textile lifting slings GeoLift can easily deal with loads up to hundreds of tons on the hook, and are made to measure and meet standards of precision. But they are still light weight and easy to handle. GeoLift are heavy load lifting slings that are based on the textile rope DynaOne® made with Dyneema®, and are comprehensively certified for safety and set international standards. Manufactured according to customer specification in order to perfectly fit the desired application.

**Elongation at WLL:** Maximum 1,8%

**Length tolerance:** Production tolerance of length +/- half rope diameter

**Material:** DynaOne® made with Dyneema® SK78

**Marking:** According to standard, Equipped with label with information according to standard. Yellow coloured sleeves to define lifting point towards crane hook. Black sleeves towards load.

**Temperature range:** -40 to 70°C

**Standard:** EN 1492-4

**Safety factor:** 7:1

Part code	WLL ton
343101000000030	10
343101500000030	15
343103000000030	30
343105000000030	50
343107000000030	70
343109000000030	90
343110000000030	100

Technical data

Higher than 100t

Art No	Code	Type	Rope Ø	Min. length	Weight at min. length	SWL	SWL	BL
			mm	m	kg	SF7	SF5	t
	HD 125t	R2	80	8,2	121	125	175	926
	HD 150t	R2	88	9,0	161	150	220	1100
	HD 175t	R1	116	11,5	250	175	245	1225
	HD 200t	R1	124	12,2	303	200	280	1400
	HD 225t	R1	132	12,9	364	225	315	1575
	HD 300t	R2	120	11,8	458	300	420	2100
	HD 325t	R2	128	12,6	556	325	455	2275
	HD 350t	R2	132	12,9	606	350	490	2450