

## Geared Trolley POWERTEX PGT-S1

### Product information



### **POWERTEX**

POWERTEX geared trolley operated by the chain. A compact and low built design with low dead weight in solid steel construction. It includes mechanical stops to ensure that the trolley is kept on the beam in case of an accident (anti-drop + anti-tilt). Fits most types of beam profiles and most brands of lifting blocks and electric hoists. Wheels with ball bearings.

Supplied with the grey label for adhering over white nameplate for use in the entertainment industry.

**Static test coefficient:** WLL x 1,5.

[... Read more](#)

**Marking:** According to standard, WLL, CE and individual serial number.

**Finish:** Black painted.


**Standard:** EN 13157

**Note:** Working handchain length is 3m as standard. Available in other lengths.

**Safety factor:** 4:1

## Geared Trolley POWERTEX PGT-S1

### Blueprint



### Technical data

| Part code       | WLL ton | Beam width mm | Wheel Ø outside/inside | Minimum radius mm | Weight kg |
|-----------------|---------|---------------|------------------------|-------------------|-----------|
| 502600101880040 | 1       | 66-188        | 96,2/68                | 1,000             | 15        |
| 502600202000040 | 2       | 88-200        | 108,2/80               | 1,100             | 22        |
| 502600302050040 | 3       | 100-205       | 131,3/100              | 1,300             | 34        |
| 502600502120040 | 5       | 114-212       | 143,7/110              | 1,400             | 49        |