

Green Pin tõsteseekel G-4161

Tootekirjeldus



- **General:** Bow shackles with screw pin.

- **Standard:** EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVA Class 2, Grade A.

- **Temperature range:** -40°C - +200°C.

- **Certification:** At no extra charges this product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 2 t can be supplied with DNV 2.1 ... [Read more](#)

Materjal: Bow and pin high tensile steel, Grade 6, quenched and tempered.

Märgistus: Vastavalt standardile, CE-tähisega

Pinnakate: Hot dipped galvanized.


Standard: EN 13889

Ohutustegur: 6:1

Klass: 6

Green Pin tõsteseekel G-4161

Blueprint



Tehnilised andmed

Tootekood	WLL tonn	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	i mm	j mm	Kaal kg
420100030580	0,33	5	6	12	5	9,5	22	16	36	29,5	26	0,02
420100050580	0,5	7	8	16,5	7	12	29	20	48,5	38	34	0,05
420100080580	0,75	9	10	20	9	13,5	32	22	56	46,5	40	0,1
420100100580	1	10	11	22,5	10	17	36,5	26	63,5	54	46	0,14
420100150580	1,5	11	13	26,5	11	19	43	29	74	59,5	51	0,19
420100200580	2	13,5	16	34	13	22	51	32	89	73	58	0,36
420100330580	3,25	16	19	40	16	27	64	43	110	89	75	0,63
420100480580	4,75	19	22	46	19	31	76	51	129	103	89	1,01
420100650580	6,5	22	25	52	22	36	83	58	144	119	102	1,5
420100850580	8,5	25	28	59	25	43	95	68	164	137	118	2,21
420100950580	9,5	28	32	66	28	47	108	75	185	153	131	3,16
420101200580	12	32	35	72	32	51	115	83	201	170	147	4,31
420101350580	13,5	35	38	80	35	57	133	92	227	186	162	5,55
420101700580	17	38	42	88	38	60	146	99	249	203	175	7,43
420102500580	25	45	50	103	45	74	178	126	300	243	216	12,84
420103500580	35	50	57	111	50	83	197	138	331	272	238	18,15
420104250580	42,5	57	65	130	57	95	222	160	377	310	274	26,29
420105500580	55	65	70	145	65	105	260	180	433	344	310	37,6