



Green Pin tõsteseekel G-4161

Tootekirjeldus

- **General:** Bow shackles with screw pin.

- **Standard:** EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVA Class 2, Grade A.

- **Temperature range:** -40°C - +200°C.

- **Certification:** At no extra charges this product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 2 t can be supplied with DNV 2.7-1 certificate.

Materjal: Bow and pin high tensile steel, Grade 6, quenched and tempered.

Märgistus: Vastavalt standardile, CE-tähisega

Pinnakate: Hot dipped galvanized.

Standard: EN 13889

Ohutustegur: 6:1

Klass: 6

Tootekood	WLL tonn	A,	B,	C,	D,	e mm	f mm	g mm	h mm	i mm	j mm	Kaal kg	Tarneaeg
420100030580	0,33	5	6	12	5	9,5	22	16	36	29,5	26	0,02	7
420100050580	0,5	7	8	16,5	7	12	29	20	48,5	38	34	0,05	7
420100080580	0,75	9	10	20	9	13,5	32	22	56	46,5	40	0,1	7
420100100580	1	10	11	22,5	10	17	36,5	26	63,5	54	46	0,14	7
420100150580	1,5	11	13	26,5	11	19	43	29	74	59,5	51	0,19	7
420100200580	2	13,5	16	34	13	22	51	32	89	73	58	0,36	3
420100330580	3,25	16	19	40	16	27	64	43	110	89	75	0,63	7
420100480580	4,75	19	22	46	19	31	76	51	129	103	89	1,01	7
420100650580	6,5	22	25	52	22	36	83	58	144	119	102	1,5	7
420100850580	8,5	25	28	59	25	43	95	68	164	137	118	2,21	3
420100950580	9,5	28	32	66	28	47	108	75	185	153	131	3,16	7
420101200580	12	32	35	72	32	51	115	83	201	170	147	4,31	3
420101350580	13,5	35	38	80	35	57	133	92	227	186	162	5,55	7
420101700580	17	38	42	88	38	60	146	99	249	203	175	7,43	7
420102500580	25	45	50	103	45	74	178	126	300	243	216	12,84	7
420103500580	35	50	57	111	50	83	197	138	331	272	238	18,15	7
420104250580	42,5	57	65	130	57	95	222	160	377	310	274	26,29	7
420105500580	55	65	70	145	65	105	260	180	433	344	310	37,6	7

Blueprint

