



Green Pin tõsteseekel G-4163

Tootekirjeldus

- **Standard:** EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVA Class 3, Grade A.
- **Temperature range:** -40°C up to +200°C.

- **Certification:** At no extra charges this product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 2 t can be supplied with DNV 2.7-1 certificate.

Materjal: Bow and pin high tensile steel, Grade 6, quenched and tempered.

Märgistus: Vastavalt standardile, CE-tähisega

Pinnakate: Hot dipped galvanized.

Standard: EN 13889

Ohutustegur: 6:1

Klass: 6

Tootekood	WLL tonn	a mm	b mm mm	c mm	dmm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	j mm mm	k mm mm	Kaal kg	Tarneaeg
420100050570	0,5	7	8	16,5	7	12	29	20	48,5	42	34	4	0,06	7
420100080570	0,75	9	10	20	9	13,5	32	22	56	50	40	5	0,11	7
420100100570	1	10	11	22,5	10	17	36,5	26	63,5	60	46	8	0,16	7
420100150570	1,5	11	13	26,5	11	19	43	29	74	67	51	11	0,22	7
420100200570	2	13,5	16	34	13	22	51	32	89	82	58	13	0,42	7
420100330570	3,25	16	19	40	16	27	64	43	110	98	75	17	0,74	7
420100480570	4,75	19	22	46	19	31	76	51	129	114	89	19	1,18	3
420100650570	6,5	22	25	52	22	36	83	58	144	130	102	22	1,77	7
420100850570	8,5	25	28	59	25	43	95	68	164	150	118	25	2,58	3
420100950570	9,5	28	32	66	28	47	108	75	185	166	131	27	3,66	7
420101200570	12	32	35	72	32	51	115	83	201	178	147	30	4,91	7
420101350570	13,5	35	38	80	35	57	133	92	227	197	162	33	6,54	7
420101700570	17	38	42	88	38	60	146	99	249	202	175	19	8,19	7
420102500570	25	45	50	103	45	74	178	126	300	249	216	23	14,22	7
420103500570	35	50	57	111	50	83	197	138	331	269	238	26	19,85	7
420104250570	42,5	57	65	130	57	95	222	160	377	301	274	29	28,33	7
420105500570	55	65	70	145	65	105	260	180	433	330	310	32	39,59	7
420108500570	85	75	83	162	73	127	329	190	527	380	340	39	62	7

Blueprint

