Lifting Solutions Group
Axel Johnson International

Green Pin vandipinguti silm-silm G-6311

Tootekirjeldus



• **Material :** drop forged high tensile steel SAE 1035 or 1045
• **Safety factor :** MBL equals 5 x WLL
• **Standard :** generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b
• **Finish :** hot dipped galvanized
• **Certification :** a works certificate, proof load test certificate and/or EC Declaration of Conformity can be supplied upon request

... *Read more*

Märgistus: CE-tähisega


Ohutustegur: 5:1

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Green Pin vandipinguti silm-silm G-6311

Blueprint



Tehnilised andmed

Tootekood	WLL tonn	Thread Inch	Take up inch	a " mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	Kaal kg
422100540250	0,54	3/8	6	3/8	292	428	183	10	13	29	49	0,48
422100100250	1	1/2	6	1/2	325	455	193	12	18	36	58	0,81
422100100255	1	1/2	9	1/2	400	608	270	12	18	36	57	1,07
422100100256	1	1/2	12	1/2	476	760	346	12	18	36	57	1,29
422100160250	1,59	5/8	6	5/8	380	503	203	14	21	45	79	1,33
422100160255	1,59	5/8	9	5/8	455	656	280	14	21	45	78	1,61
422100160256	1,59	5/8	12	5/8	531	808	356	14	21	45	78	1,96
422100240250	2,36	3/4	6	3/4	413	532	214	17	26	54	89	2,03
422100240255	2,36	3/4	9	3/4	490	685	291	17	26	54	89	2,47
422100240256	2,36	3/4	12	3/4	564	837	367	17	26	54	88	2,9
422100240257	2,36	3/4	18	3/4	718	1 143	519	17	26	54	89	3,94
422100330250	3,27	7/8	12	7/8	604	870	377	20	32	61	101	4,31
422100330255	3,27	7/8	18	7/8	756	1 174	529	20	32	61	101	5,51
422100450255	4,54	1	6	1	498	604	234	24	37	76	118	4,35
422100450256	4,54	1	12	1	649	909	387	24	37	76	117	5,75
422100450257	4,54	1	18	1	801	1 215	539	24	37	76	117	7,27
422100450250	4,54	1	24	1	952	1 518	692	24	37	76	116	7,52
422100690250	6,9	1 1/4	12	1 1/4	712	985	385	29	47	91	145	9,28
422100690255	6,9	1 1/4	18	1 1/4	862	1 287	537	29	47	91	144	11,1
422100690256	6,9	1 1/4	24	1 1/4	1 015	1 592	690	29	47	91	144	12,1
422100970250	9,71	1 1/2	12	1 1/2	756	1 023	401	32	55	106	156	14,2
422100970255	9,71	1 1/2	18	1 1/2	916	1 335	553	32	55	106	160	15,8

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Green Pin vandipinguti silm-silm G-6311

Tehnilised andmed

Tootekood	WLL tonn	Thread Inch	Take up inch	a " mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	Kaal kg
422100970256	9,71	1 1/2	24	1 1/2	1 065	1 636	706	32	55	106	158	17,1
422101270250	12,7	1 3/4	18	1 3/4	1 020	1 396	577	38	61	120	197	23,1
422101270255	12,7	1 3/4	24	1 3/4	1 171	1 703	730	38	61	120	196	26,3
422101680250	16,8	2	24	2	1 264	1 784	748	46	69	147	230	40,7
422102720250	27,2	2 1/2	24	2 1/2	1 430	1 934	802	51	80	165	274	64
422103400250	34	2 3/4	24	2 3/4	1 450	1 988	802	57	84	178	284	88

© November 2026 - All Rights Reserved