



Green Pin vandipinguti konks-konks G-6312

Tootekirjeldus

- **Material** : drop forged high tensile steel SAE 1035 or 1045
- **Safety factor** : MBL equals 5 x WLL
- **Standard** : generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b
- **Finish** : hot dipped galvanized
- **Certification** : a works certificate, proof load test certificate and/or EC Declaration of Conformity can be supplied upon request

Märgistus: CE-tähisega

Ohutustegur: 5:1

Tootekood	WLL tonn	Keere	Take up inch	a" mm	b mm mm	c mm	dmm mm	e mm mm	f mm mm	g mm mm	Kaal kg	Tarneaeg
422100540310	0,54	3/8	6	3/8	278	415	13	16	15	42	0,53	7
422100680310	0,68	1/2	12	1/2	456	739	13	19	16	47	1,34	7
422100100310	1	1/2	6	1/2	305	434	16	22	16	48	0,93	7
422100100315	1	1/2	9	1/2	380	587	16	22	16	47	1,16	7
422100140310	1,36	3/4	9	3/4	468	664	20	27	24	78	2,49	7
422100160310	1,59	5/8	6	5/8	356	479	16	23	21	67	1,4	7
422100160316	1,59	5/8	12	5/8	507	784	16	23	21	66	1,79	7
422100160315	1,59	5/8	9	5/8	431	632	20	24	21	66	1,96	7
422100230315	2,27	1	18	1	778	1 191	26	35	31	106	6,5	7
422100230316	2,27	1	24	1	928	1 495	26	35	31	105	8,13	7
422100240310	2,36	3/4	6	3/4	393	511	22	27	24	78	2,04	7
422100240315	2,36	3/4	12	3/4	544	816	22	27	24	78	3,27	7
422100450310	4,54	1	6	1	479	586	26	35	31	109	4,23	7
422100450315	4,54	1	12	1	625	886	26	35	31	106	6,64	7

Blueprint

