Lifting Solutions Group
Axel Johnson International

Green Pin vandipinguti silm-konks G-6314

Tootekirjeldus



- **Material :** drop forged high tensile steel SAE 1035 or 1045
- **Safety factor :** MBL equals 5 x WLL
- **Standard :** generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b
- **Finish :** hot dipped galvanized
- **Certification :** a works certificate, proof load test certificate and/or EC Declaration of Conformity can be supplied upon request.

... *Read more*

Märgistus: CE-tähisega


Ohutustegur: 5:1

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Green Pin vandipinguti silm-konks G-6314

Blueprint



Tehnilised andmed

Tootekood	WLL tonn	Keere	Take up inch	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	Kaal kg
422100540330	0,54	3/8	6	285	422	13	16	15	10	13	29	49	0,47
422100680330	0,68	1/2	12	466	750	13	19	16	12	18	36	57	1,28
422100100330	1	1/2	6	315	445	16	22	16	12	18	36	58	0,82
422100100335	1	1/2	9	390	598	16	22	16	12	18	36	57	1,06
422100100336	1,02	5/8	6	368	491	16	23	21	14	21	45	79	1,31
422100100337	1,02	5/8	12	519	796	16	23	21	14	21	45	78	1,71
422100140330	1,36	3/4	9	479	675	20	27	24	17	26	54	89	4,49
422100160330	1,59	5/8	9	443	644	20	24	21	14	21	45	78	1,56
422100230330	2,27	1	6	488	595	26	35	31	24	36	75	118	3,87
422100230335	2,27	1	18	789	1 202	26	35	31	24	36	75	117	6
422100230336	2,27	1	24	939	1 506	26	35	31	24	36	75	116	7,52
422100240330	2,36	3/4	6	403	521	22	27	24	17	26	54	89	2,04
422100240335	2,36	3/4	12	554	827	22	27	24	17	26	54	88	2,3
422100240336	2,36	3/4	18	707	1 133	22	27	24	17	26	54	89	2,85
422100450330	4,54	1	12	636	897	26	35	31	24	36	75	117	5,09

© November 2026 - All Rights Reserved