

Green Pin vandipinguti silm-kahvel G-6315

Tootekirjeldus



- **Material** : drop forged high tensile steel SAE 1035 or 1045
- **Safety factor** : MBL equals 5 x WLL
- **Standard** : generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b
- **Finish** : hot dipped galvanized
- **Certification** : a works certificate, proof load test certificate and/or EC Declaration of Conformity can be supplied upon request
- **Note** : jaw ends up to and including 5/8" are fitted with bolts and nuts, sizes 3/4" and up are equipped with pins and cotters.


... [Read more](#)

Märgistus: CE-tähisega

Ohutustegur: 5:1

Green Pin vandipinguti silm-kahvel G-6315

Blueprint



Tehnilised andmed

Tootekood	WLL tonn	Thread Inch	Take up inch	a " mm	b mm mm	c mm	dmm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	j mm mm	k mm mm	l mm mm	Kaal kg
422100540290	0,54	3/8	6	3/8	283	418	12	21	8	9	21	10	13	29	49	0,52
422100100290	1	1/2	6	1/2	315	446	16	26	10	11	25	12	18	36	58	0,88
422100100295	1	1/2	9	1/2	390	598	16	26	10	11	25	12	18	36	57	1,13
422100100296	1	1/2	12	1/2	466	751	16	26	10	11	25	12	18	36	57	1,37
422100160290	1,59	5/8	6	5/8	363	486	18	32	13	14	33	14	21	45	79	1,55
422100160295	1,59	5/8	9	5/8	438	639	18	32	13	14	33	14	21	45	78	1,84
422100160296	1,59	5/8	12	5/8	514	790	18	32	13	14	33	14	21	45	78	2,17
422100240290	2,36	3/4	6	3/4	391	510	24	38	16	16	41	17	26	54	89	2,28
422100240295	2,36	3/4	9	3/4	467	663	24	38	16	16	41	17	26	54	89	2,82
422100240296	2,36	3/4	12	3/4	542	815	24	38	16	16	41	17	26	54	88	2,95
422100240297	2,36	3/4	18	3/4	694	1 120	24	38	16	16	41	17	26	54	89	3,3
422100330290	3,27	7/8	12	7/8	583	848	27	42	19	19	48	20	32	61	101	4,35
422100330295	3,27	7/8	18	7/8	735	1 153	27	42	19	19	48	20	32	61	101	5,46
422100450297	4,5	1	24	1	928	1 494	31	50	22	20	54	24	37	76	116	8,35
422100450296	4,54	1	6	1	473	579	31	50	22	20	54	24	37	76	118	4,66
422100450290	4,54	1	12	1	624	884	31	50	22	20	54	24	37	76	117	5,94
422100450295	4,54	1	18	1	776	1 190	31	50	22	20	54	24	37	76	117	7,98
422100690290	6,9	1 1/4	12	1 1/4	677	950	44	71	29	26	68	29	47	91	145	10,4
422100690295	6,9	1 1/4	18	1 1/4	833	1 258	44	71	29	26	68	29	47	91	144	11
422100690296	6,9	1 1/4	24	1 1/4	989	1 566	44	71	29	26	68	29	47	91	144	12,9
422100970290	9,71	1 1/2	12	1 1/2	716	983	52	71	35	28	80	32	55	106	156	13,1
422100970295	9,71	1 1/2	18	1 1/2	871	1 290	52	71	35	28	80	32	55	106	160	14,7

Green Pin vandipinguti silm-kahvel G-6315

Tehnilised andmed

Tootekood	WLL tonn	Thread Inch	Take up inch	a " mm	b mm mm	c mm	dmm mm	e mm mm	f mm mm	g mm mm	h mm mm	i mm mm	j mm mm	k mm mm	l mm mm	Kaal kg
422100970296	9,71	1 1/2	24	1 1/2	1 023	1 594	52	71	35	28	80	32	55	106	158	17,8
422101270290	12,7	1 3/4	18	1 3/4	979	1 356	60	86	41	33	90	38	61	120	197	22,3
422101270295	12,7	1 3/4	24	1 3/4	1 130	1 662	60	86	41	33	90	38	61	120	196	27,5
422101680290	16,8	2	24	2	1 208	1 728	63	93	51	40	107	46	69	147	230	42,9
422102720290	27,2	2 1/2	24	2 1/2	1 343	1 899	75	114	57	41	143	51	80	165	274	68
422103400290	34	2 3/4	24	2 3/4	1 399	1 953	90	110	70	41	158	57	84	178	284	91