

Green Pin vandipinguti kahvel-kahvel G-6323

Tootekirjeldus



- **Material** : drop forged high tensile steel SAE 1035 or 1045
- **Safety factor** : MBL equals 5 x WLL
- **Standard** : generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b
- **Finish** : hot dipped galvanized
- **Certification** : a works certificate, proof load test certificate and/or EC Declaration of Conformity
can be supplied upon request


... [Read more](#)

Märgistus: CE-tähisega

Ohutustegur: 5:1

Green Pin vandipinguti kahvel-kahvel G-6323

Blueprint



Tehnilised andmed

Tootekood	WLL tonn	Thread Inch	Take up inch	a " mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	Kaal kg
422100050300	0,54	3/8	6	3/8	273	409	304	12	21	7	9	21	0,55
422100100300	1	1/2	6	1/2	304	435	343	16	26	10	11	25	0,96
422100100305	1	1/2	9	1/2	379	588	418	16	26	10	11	25	1,18
422100100306	1	1/2	12	1/2	455	740	494	16	26	10	11	25	1,5
422100160300	1,59	5/8	6	5/8	346	469	406	18	32	13	14	33	1,75
422100160305	1,59	5/8	9	5/8	421	622	480	18	32	13	14	33	2,14
422100160306	1,59	5/8	12	5/8	498	774	557	18	32	13	14	33	2,43
422100240300	2,36	3/4	6	3/4	369	487	439	24	38	16	16	41	2,7
422100240305	2,36	3/4	9	3/4	444	640	514	24	38	16	16	41	3,23
422100240306	2,36	3/4	12	3/4	520	792	590	24	38	16	16	41	3,57
422100240307	2,36	3/4	18	3/4	670	1 096	740	24	38	16	16	41	4,55
422100330300	3,27	7/8	12	7/8	561	826	638	27	42	19	19	48	5,22
422100330305	3,27	7/8	18	7/8	713	1 132	790	27	42	19	19	48	6,56
422100450305	4,54	1	6	1	447	554	532	31	50	22	20	54	5,54
422100450306	4,54	1	12	1	598	859	683	31	50	22	20	54	6,96
422100450307	4,54	1	18	1	750	1 168	835	31	50	22	20	54	8,4
422100450300	4,54	1	24	1	903	1 470	988	31	50	22	20	54	8,9
422100690300	6,9	1 1/4	12	1 1/4	643	916	748	44	71	28	26	68	11,9
422100690305	6,9	1 1/4	18	1 1/4	805	1 230	910	44	71	28	26	68	13,6
422100690306	6,9	1 1/4	24	1 1/4	964	1 541	1 069	44	71	28	26	68	14,2
422100970300	9,71	1 1/2	12	1 1/2	675	942	806	52	71	35	28	80	18,5
422100970305	9,71	1 1/2	18	1 1/2	825	1 244	956	52	71	35	28	80	19,3

Green Pin vandipinguti kahvel-kahvel G-6323

Tehnilised andmed

Tootekood	WLL tonn	Thread Inch	Take up inch	a " mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	Kaal kg
422100970306	9,71	1 1/2	24	1 1/2	980	1 551	1 111	52	71	35	28	80	22
422101270300	12,7	1 3/4	18	1 3/4	938	1 316	1 092	60	86	41	33	90	30
422101270305	12,7	1 3/4	24	1 3/4	1 089	1 621	1 243	60	86	41	33	90	33
422101680300	16,8	2	24	2	1 153	1 673	1 338	63	93	50	40	107	50
422102720300	27,2	2 1/2	24	2 1/2	1 255	1 831	1 480	75	114	57	41	143	92
422103400300	34	2 3/4	24	2 3/4	1 348	1 882	1 604	90	110	70	41	158	109