

Tõstesilm 8-291K Yoke

Tootekirjeldus



The lifting eye rotates through 360° adjustable in the direction of the load.

Märgistus: Vastavalt standardile, CE-tähisega

Standard: EN 1677-1

Ohutustegur: 4:1

Klass: 10

Tootekood	WLL tonn	Thread mm	Pingutusmoment (Nm)	Pitch DIN 13	A,	B,	C,	D,	E,	F,	G,	H,	J,	S mm	W mm	M mm	Kaal kg	Tarneaeg
421100030620	0,3	M 8	10	1,25	38	25	9	9	12	25	24	6	41	6	44	M 8	0,1	7
421100040620	0,4	M 10	10	1,5	38	25	9	9	15	25	24	6	41	6	44	M 10	0,1	3
421100080620	0,75	M 12	10	1,75	45	30	10	11	18	33	30	9	47	8	52	M 12	0,2	3
421100150620	1,5	M 16	30	2	52	35	14	13	24	35	34	11	56	10	61	M 16	0,4	7
421100230620	2,3	M 20	70	2,5	60	40	16	15	30	44	37	15	65	12	70	M 20	0,6	7
421100320620	3,2	M 24	150	3	72	49	19	18	36	53	47	19	78	14	84	M 24	1,1	7
421100450620	4,5	M 30	350	3,5	91	61	24	22	45	62	59	23	95	17	105	M 30	2,1	3
421100700620	7	M 36	410	4	110	73	29	27	54	76	72	31	114	22	126	M 36	3,7	3
421100900620	9	M 42	550	4,5	128	83	34	32	63	89	81	38	132	24	147	M 42	5,8	7
421101200620	12	M 48	550	5	145	95	38	37	72	105	94	44	150	27	168	M 48	8,6	7
421101600620	16	M 56	800	5,5	148	102	40	43	84	124	92	49	166	27	178	M 56	11	7
421101800620	18	M 64	800	6	148	102	40	43	96	124	92	49	166	27	178	M 64	11,8	7

Blueprint

