

STOBITEX Wear Protection Sleeve PU-2/double side



Tootekirjeldus

Special wear protection for roundslings and webbing slings, intended for lift of load with cutting edges. Extremely good cutting resistance and high wear strength.

Also available as single sided sheathes, STOBITEX Wear Protection Sleeve PU-1/single.

Tootekood	Kood	For 2 layer lifting mm	For lashings	For 4 layer lifting mm	For webbing sling t	a mm	h mm	i mm	w mm	Kaal kg	Tarneaeg
8025PU2666043	PU-2 66/60/4/3	-	50	-	-	70	4	60	3	0,85	7
8025PU25040105	PU-2 50/40/10/5	30	35	-	-	50	10	40	5	1,1	7
8025PU27060125	PU-2 70/60/12/5	50	-	-	-	70	12	60	5	1,45	7
8025PU28070125	PU-2 80/70/12/5	60	-	-	-	80	12	70	5	1,6	7
8025PU29585125	PU-2 95/85/12/5	75	75	-	-	95	12	85	5	2	7
8025PU2110100125	PU-2 110/100/12/5	90	-	-	-	110	12	100	5	2,1	7
8025PU2145135125	PU-2 145/135/12/5	120	-	-	-	145	12	135	5	2,8	7
8025PU2170160125	PU-2 170/160/12/5	150	-	-	-	170	12	160	5	3,4	7

8025PU2200190125	PU-2 200/190/12/5	180	-	-	-	200	12	190	5	3,8	7
8025PU2330320158	PU-2 330/320/15/8	300	-	-	-	330	15	320	8	7,2	7
8025PU2330320308	PU-2 330/320/30/8	-	-	300	-	330	30	320	8	7,8	7
8025PU2330320458	PU-2 330/320/45/8	-	-	-	20	330	45	320	8	8,4	7
8025PU25040205	PU-2 50/40/20/5	-	-	30	-	50	20	40	5	-	7
8025PU27060175	PU-2 70/60/17/5	-	-	50	-	70	17	60	5	-	7
8025PU28575175	PU-2 85/75/17/5	-	-	-	1	85	17	75	5	-	7
8025PU28070245	PU-2 80/70/24/5	-	-	60	-	80	24	70	5	-	7
8025PU29585245	PU-2 95/85/24/5	-	-	75	2	95	12	85	5	-	7
8025PU2110100175	PU-2 110/100/17/5	-	-	-	3	110	17	100	5	-	7
8025PU2110100245	PU-2 110/100/24/5	-	-	90	-	110	24	100	5	-	7
8025PU2145135245	PU-2 145/135/24/5	-	-	120	-	145	24	135	5	-	7
8025PU2170160175	PU-2 170/160/17/5	-	-	-	6	170	17	160	5	-	7
8025PU2170160245	PU-2 170/160/24/5	-	-	150	-	170	24	160	5	-	7
8025PU2200190175	PU-2 200/190/17/5	-	-	-	8	200	17	190	5	-	7
8025PU2200190245	PU-2 200/190/24/5	-	-	180	-	200	24	190	5	-	7
8025PU2230220365	PU-2 230/220/36/5	-	-	-	10	230	36	220	5	-	7
8025PU2260250158	PU-2 260/250/15/8	240	-	-	-	260	15	250	8	-	7
8025PU2290280308	PU-2 290/280/30/8	-	-	240	15	290	30	280	8	-	7

Blueprint

