



Crosby pöörits S1 kahvel / konks

Tootekirjeldus

Design: Jaw and hook swivel with tapered roller thrust bearing. Suitable for frequent rotation under load.

Proof load: 2 x WLL.

Important: Crosby swivels should only be used with the recommended wire rope.

Märgistus: CE-tähisega, WLL.

Pinnakate: Painted.

Ohutustegur: 5:1

Tootekood	Trossi Ø mm	WLL tonn	Swivel No	A mm	F mm	G mm	H mm	J mm	K mm	L mm	M mm	N mm	O mm	P mm	V mm	Kaal kg	Tarneaeg
422500300280	13	3	3-S-1	291	123	70	19,1	22,4	41,1	38,9	35,8	33,3	25,4	36,6	28,4	4,45	7
422500500280	16	5	5-S-1	339	160	76	22,4	25,4	57	49,3	42,9	41,1	28,4	46	36,6	7,04	7
422500850280	19	8,5	8-S-1	418	192	102	25,4	39,5	71,5	62,5	56,5	54	35,1	57	41,1	13,3	7
422501000280	22	10	10-S-1	502	212	114	38,1	44,5	86	66	61	89	44,5	66	49,3	21,2	7
422501500280	26	15	15-S-1	565	263	127	38,1	44,5	86	71,5	81	89	44,5	76	60,5	33,5	7
422502500280		25	25-S-1	680	346	152	51	51	117	87,5	92	93,5	60,5	93	76	64	7
422503500280		35	35-S-1	760	357	165	51	51	117	98,5	95,5	93,5	60,5	116	81	100	7
422504500280		45	45-S-1	891	392	178	57	63,5	127	121	108	102	76	129	82,5	114	7

Blueprint

