



Crosby pöörits S2 kahvel / kahvel

Tootekirjeldus

Design: Jaw and jaw swivel with tapered roller thrust bearing. Suitable for frequent rotation under load.

Proof load: 2 x WLL.

Important! Crosby swivels should only be used with the recommended wire rope.

Märgistus: CE-tähisega, WLL.

Pinnakate: Painted.

Ohutustegur: 5:1

Tootekood	Trossi Ø mm	WLL tonn	Swivel No	B mm	G mm	H mm	J mm	K mm	N mm	O mm	Kaal kg	Tarneaeg
422500300080	13	3	3-S-2	236	70	19,1	22,4	41,1	33,3	25,4	4,37	7
422500500080	16	5	5-S-2	262	76	22,4	25,4	57	41,1	28,4	6,21	7
422500850080	19	8,5	8-S-2	321	102	25,4	39,5	71,5	54	35,1	11,9	7
422501000080	22	10	10-S-2	426	114	38,1	44,5	86	89	44,5	20,8	7
422501500080	26	15	15-S-2	435	127	38,1	44,5	86	89	44,5	28,5	7
422502500080	-	25	25-S-2	527	152	51	51	117	93,5	60,5	64	7
422503500080	-	35	35-S-2	527	165	51	51	117	93,5	60,5	70	7
422504500080	-	45	45-S-2	641	178	57	63,5	127	102	76	107	7

Blueprint

