

Tõstesilm SS FE DSR

Tootekirjeldus



SS FE DSR M Stainless steel female double swivel ring.

The stainless steel version of the double swivel ring, FE.DSR, can be used in humid, corrosive, chemical, maritime environment. Its double articulation allows it to line up perfectly with the sling.

Features:

- Rotatable under load.

... [Read more](#)


Märgistus: Vastavalt standardile, CE-tähisega

Standard: EN 1677-1
except grade/WLL

Ohutustegur: 5:1

Tõstesilm SS FE DSR

Blueprint



Tehnilised andmed

Tootekood	WLL tonn	Keere	Pingutusmoment (Nm)	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L max. mm	S mm	Kaal kg
4215SSFEDSRM8	0,3	M 8 (x1,25)	6	43	40	45	53	38	17	76	13	43	20	0,9
4215SSFEDSRM10	0,5	M 10 (x1,50)	10	43	40	45	53	38	17	76	13	43	20	0,9
4215SSFEDSRM12	0,8	M 12 (x1,75)	15	43	40	45	53	38	17	76	13	43	20	0,9
4215SSFEDSRM14	1	M 14 (x2)	30	43	40	45	53	38	17	76	13	43	20	0,9
4215SSFEDSRM16	1,4	M 16 (x2)	50	43	40	45	53	38	17	76	13	43	20	0,9
4215SSFEDSRM18	1,4	M 18 (x2,5)	70	62	55	58	83	56	25	115	19	62	24	2,6
4215SSFEDSRM20	1,4	M 20 (x2,5)	100	62	55	58	83	56	25	115	19	62	24	2,6
4215SSFEDSRM22	2,2	M 22 (x2,5)	120	62	55	58	83	56	25	115	19	62	24	2,6