

Anchor Point ABS - Lock X-Rivet

Tootekirjeldus



Anchorage point - designed for riveting onto sandwich and trapezoidal sheeting.
Anchor point ABS-Lock X-Rivet is simply riveted on top of roof membrane using 14 watertight blind rivets.

The 2 different base plates can be used for different seam intervals.

- LX-SW-N-250 -> Distance between the holes: 180-250 mm
- LX-SW-N-333 -> Distance between the holes: 280-333 mm

Also available as an intermediate ("ZW") bracket in a lifeline system in 2 heights.

- LX-SW-N-...-ZW -> Bracket height 150 mm
- LX-SW-N-...-ZW-350 -> Bracket height 350 mm

For steel plating: ≥ 0.45 mm;

Aluminium: ≥ 0.8 mm.

Force directions: Lateral.

Substructure: Sandwich, trapezoidal sheeting, profile roof.

Attachment: Riveted

Application: Profile Roof, flat roofs

Märgistus: Vastavalt standardile

Standard: EN 795, CEN/TS/16415

| Tootekood | Kood | Max. number of persons | Kaal kg | Tarneaeg |
|-------------------|-------------------------|-------------------------------|----------------|-----------------|
| 8415LXSWN250 | 19.10LX-SW-N-250 | 3 | 2,012 | 7 |
| 8415LXSWN333 | 19.10LX-SW-N-333 | 3 | 2,129 | 7 |
| 8415LXSWN250ZW | 19.10LX-SW-N-250-ZW | 3 | 2,34 | 7 |
| 8415LXSWN333ZW | 19.10LX-SW-N-333-ZW | 3 | 2,457 | 7 |
| 8415LXSWN250ZW350 | 19.10LX-SW-N-250-ZW-350 | 3 | 2,712 | 7 |
| 8415LXSWN333ZW350 | 19.10LX-SW-N-333-ZW-350 | 3 | 2,829 | 7 |