

## Anchor Point ABS-Lock X-SW

### Tootekirjeldus



Stainless steel anchor point ABS-Lock X-SW (Ø 16 mm) with base plate (372 x 200 mm) is a fall protection solution developed for usage on top of a sandwich roof an trapezoidal sheeting (negative). To install this anchor, all you need is a minimum sandwich profile (steel) depth of 0.5 mm.

The anchor point is easily installed using the 4 specially prepared toggle bolts included in the package. The pre-drilled holes in the ABS-Lock X-SW base plate are set at different intervals - allowing it to be installed on a variety of profiles with different seam intervals. Distance between the bores: 280 to 333 mm.

**Force directions:** Lateral

**Substructure:** Sandwich

**Attachment:** Toggle bolts

**Application:** Profile roof, flat roofs

**Märgistus:** Vastavalt standardile, CE-tähisega

**Standard:** EN 795-A, CEN/TS/16415

| Tootekood   | Max. number of persons | Pikkus mm | Kaal kg | Tarneaeg |
|-------------|------------------------|-----------|---------|----------|
| 8415LXSW150 | 3                      | 150       | 2,844   | 7        |
| 8415LXSW300 | 3                      | 300       | 3,119   | 7        |
| 8415LXSW400 | 3                      | 400       | 3,702   | 7        |