

KITO elektriline kett-tali tüüp ER2, ühe kiirusega

Tootekirjeldus



Electric chain hoist with hook suspension

General: The ER2 Electric Chain Hoists are durable, safe and easy to use hoists. It has a top hook or overhead mounting suspension, aluminium die-cast body, electromagnetic brake and a canvas chain container. It lifts from 10 tons up to 20 tons.

Standard configuration:

- 400 V/50 Hz
- Contactor control for single speed
- CH-Meter: operating hours/number of starts
- Ergonomic push button control
- Upper-lower limit switch
- Nickel-plated load chain class grade 80 (DAT) in accordance with Norm EN 818-7
- Thermal protector
- Carbon friction clutch > 400 V/50 Hz


Options:

- 500 V/Contactor control
- 230 V/50 Hz/60 Hz, 3 phase
- Rubber bumpers for motorized trolleys
- Additional mechanical brake
- Electrical overload limiter
- Acoustic overload signal
- Radio remote control
- Variable speed control
- Level limit switch
- Steel chain container
- Trolley versions: motorized, geared and plain

... [Read more](#)

KITO elektriline kett-tali tüüp ER2, ühe kiirusega

Blueprint



Tehnilised andmed

Kood	WLL tonn	Keti languste arv	Motor kW	Lifting motor Rating (%ED)	Tõstekiirus* (m/min) 50Hz	ISO/FEM klass	Lisakaal 1m tõstekõrguse kohta	Tõstekett mm	Kaal kg
ER2-1005	10	4	3.5x2	60	2,9	M4/1Am	11	11,2 x 31,3	303
ER2-1505	15	6	3.5x2	60	1,9	M4/1Am	17	11,2 x 31,3	404
ER2-2005	20	8	3.5x2	60	1,4	M4/1Am	22	11,2 x 31,3	476

WLL tonn	Kood	Min. kõrgus C mm	D mm	a mm	b mm	w mm	g mm
10	ER2-100S	1370	1210	798	849	956	80
15	ER2-150S	1595	1520	798	1022	1129	86
20	ER2-200S	1710	1600	798	1198	1305	102