

Käsivints hammasülekandega MANIBOX GR

Tootekirjeldus



Hand spur gear winches from 300 to 2750 kg for daily use.

Applications:

- Industry
- Auditoriums, theatre scenery
- Water treatment, water dams
- Sports rooms
- Hanging chandeliers

Technical properties:

- Compact and rugged construction with steel frame.
- Machined parts.
- Steel or cast iron drum depending on models.
- Flat mounted or wall mounted positions for GR 300/530/500.
- 4 fixation points.
- Fully protected gear system.
- Removable crank positioned on the left hand side for the GR 300/530/500/750 and on the right hand side for the GR 1000/1450/2000/2750.
- Free spooling drum, only when not in load.
- Composite material automatic brake. - Failsafe system for correct rope winding direction (patented)

Optional:

Wire rope and hook.


[... Read more](#)

Märgistus: Vastavalt standardile, CE-tähisega

Standard: EN 13157

Käsivints hammasülekandega MANIBOX GR

Blueprint



Tehnilised andmed

Tootekood	WLL tonn	Trossi Ø mm	Capacity 1st layer kg	Number of layers	Lift per crank revolution mm	Rakendatav kätejõud max. kg	Max. drum capacity m	Drum Ø mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	K mm	Lg mm	S mm	T mm	Kaal kg
501300030000140	0,3	5	500	6	30,5	12,6	38	62	249	400	190	217	240	200	145	144	122	184	76	15
501300050000140	0,5	7	750	4	31,5	12,5	18	62	249	400	190	217	240	200	145	144	122	184	76	15
501300530000140	0,53	6	530	1	30,5	12,5	4	62	249	400	190	217	240	200	145	144	122	184	76	15
501300750000140	0,75	7	750	1	31,5	19	3	62	249	400	190	217	240	200	-	144	122	-	-	15
501300100000140	1	9	1 450	4	16	14,5	30	103,5	410	485	305	300	340	370	-	236	176	-	-	44
501300150000140	1,45	10	1 450	1	16	14,5	5	103,5	410	485	305	300	340	370	-	236	176	-	-	44
501300200000140	2	13	2 750	3	9,5	16,5	25	121	510	585	360	400	340	440	-	325	237,5	-	-	83
501300280000140	2,75	13	2 750	1	9,5	16,5	6	121	510	585	360	400	340	440	-	325	237,5	-	-	83