

Keevitatav tõsteaas tüüp PLE

Tootekirjeldus



General: Weldable lifting point. High-tensile eyebolts pewag profilift eta, for welding onto machine parts or vehicle bodies. Ideal for hanging of lifting and lashing parts. Due to the integrated spring, the ring will be kept in each requested position. The instructions according to DIN EN ISO 14341 are valid for the welding. The welding may only be carried out by a welding operator with a valid qualification according to EN 287-1.

The lifting points will be packed individually and together with a user manual and welding instructions

Standard: The weldable lifting point PLE is manufactured according to EG-Machine Directive 2006/42/EG and tested according to EN 1677-1.

Permissible usage

Load capacity acc. to the inspection certificate respectively table of WLL in the mentioned directions of pull (see picture 1 and 2).

Non permissible usage

Make sure when choosing the assembly that improper load can not arise e.g. if:

- The direction of pull is obstructed
- Direction of pull is not in the foreseen area
- Loading ring rests against edges and load

... [Read more](#)

Materjal: Alloy steel grade 8.

Märgistus: Vastavalt standardile, CE-tähisega, WLL and the load capacity is clearly marked on the welding pad.


Pinnakate: Painted.

Standard: EN 1677-1

Ohutustegur: 4:1

Keevitatav tõsteaas tüüp PLE

Blueprint



Tehnilised andmed

Tootekood	Kood	WLL tonn	a mm	b mm	c mm	d mm	e mm	f mm	h mm	i mm	Kaal kg
42154021831	PLE/N 6	1,12	36	40	62	11	67	42	26	35	0,31
42154021832	PLE/N 8	2	37	42	69	13	73	45	28	37	0,4
42154021833	PLE/N 10	3,15	41	45	78	16,5	80	47	34	40	0,63
42154015215	PLE/N 13	5,3	61	55	99	22	97	53	44	50	1,46
42154021835	PLE/N 16	8	63	70	120	25	120	73	48	64	2,3
42154021836	PLE/N 22	15	89	97	163	33	163	92	70	90	5,4