

Turnbuckles Eye - Hook G-6314, Green Pin®

Product information

The Green Pin® EH Turnbuckle is a turnbuckle with eye-hook end-fittings. One of the unique features of Green Pin® Turnbuckles such as this one is that they can be used for both lifting and lashing. Galvanization of the Green Pin® EE Turnbuckle ensures its long-term durability. The turnbuckle is available in a range with a diameter thread 3/8" (take up of 6") up to 1" (take up of 24").

- **Standard:** generally to ASTM F1145-92 formerly U.S. Federal Specification FF-T-791b
- **Certification:** a works certificate, proof load test certificate and/or EC Declaration of Conformity can be supplied upon request.

Marking: CE-marked

Safety factor: 5:1

Код товара	WLL ton	Thread	Take up inch	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	Вес kg	Delivery time
422100540330	0,54	3/8	6	285	422	13	16	15	10	13	29	49	0,47	7
422100680330	0,68	1/2	12	466	750	13	19	16	12	18	36	57	1,28	7
422100100330	1	1/2	6	315	445	16	22	16	12	18	36	58	0,82	7
422100100335	1	1/2	9	390	598	16	22	16	12	18	36	57	1,06	7
422100100336	1,02	5/8	6	368	491	16	23	21	14	21	45	79	1,31	7
422100100337	1,02	5/8	12	519	796	16	23	21	14	21	45	78	1,71	7
422100140330	1,36	3/4	9	479	675	20	27	24	17	26	54	89	4,49	7
422100160330	1,59	5/8	9	443	644	20	24	21	14	21	45	78	1,56	7
422100230330	2,27	1	6	488	595	26	35	31	24	36	75	118	3,87	7
422100230335	2,27	1	18	789	1 202	26	35	31	24	36	75	117	6	7
422100230336	2,27	1	24	939	1 506	26	35	31	24	36	75	116	7,52	7
422100240330	2,36	3/4	6	403	521	22	27	24	17	26	54	89	2,04	7
422100240335	2,36	3/4	12	554	827	22	27	24	17	26	54	88	2,3	7
422100240336	2,36	3/4	18	707	1 133	22	27	24	17	26	54	89	2,85	7
422100450330	4,54	1	12	636	897	26	35	31	24	36	75	117	5,09	7

Blueprint

