



Swivel Jaw / Jaw Crosby S2

Product information

Design: Swivel with jaws equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- All jaws complete with bolts, nuts and cotter pins.
- Other types and capacities up to 1250 t available on demand.

Marking: CE-marked

Safety factor: 5:1

Код товара	Rope Ø range mm	WLL ton	Swivel No	B mm	G mm	H mm	J mm	K mm	N mm	O mm	Bec kg	Delivery time
422500300080	13	3	3-S-2	236	70	19,1	22,4	41,1	33,3	25,4	4,37	7
422500500080	16	5	5-S-2	262	76	22,4	25,4	57	41,1	28,4	6,21	7
422500850080	19	8,5	8-S-2	321	102	25,4	39,5	71,5	54	35,1	11,9	7
422501000080	22	10	10-S-2	426	114	38,1	44,5	86	89	44,5	20,8	7
422501500080	26	15	15-S-2	435	127	38,1	44,5	86	89	44,5	28,5	7
422502500080		25	25-S-2	527	152	51	51	117	93,5	60,5	64	7
422503500080		35	35-S-2	527	165	51	51	117	93,5	60,5	70	7
422504500080		45	45-S-2	641	178	57	63,5	127	102	76	107	7

Blueprint

