



Chain Block POWERTEX PCB-S1

Product information

POWERTEX



Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Compact, lightweight construction.
- Durable all steel construction with powder coated finish and plated frame components.
- Safe, well covered automatic load reaction brake.
- Sealed ball bearings on the chain wheel maximise efficiency and serviceability.
- European made COROLIM[®] protected load chain.
- Corrosion resistance of the chain is equivalent to ISO944-9 C5High / ISO9223 C3
- Bottom hook with ball bearing.
- RFID equipped (chip) for easy service and inspection.
- QR code for on-site access to Multilanguage user manuals.
- User manuals in 14 languages included.
- Fulfills the Machinery Directive 2006/42/EC.
- Comply fully with the EN norms 13157 and 818-7.
- Testcertificate enclosed.

Marking: According to standard

Standard: EN 13157, EN 818-7

Safety factor: 4:1

Код товара	WLL ton	Lifting height m	Load chain Ø mm	Number of falls	A mm	B mm	C mm	Ø mm	E mm	H mm	Bec kg	Delivery time
500100030300070	0,25	3	4 x 12	1	106	68	108	18	20	280	6,4	7
500100050300070	0,5	3	5 x 15	1	128	75	130	20	22	280	8,9	3
500100100300070	1	3	6,3 x 19,1	1	142	76	150	25	26	330	12	7
500100200300070	2	3	8 x 24	1	175	88	185	33	35	385	19,5	7
500100300300070	3	3	10 x 30	1	195	95	226	36	37	435	29,4	7
500100500300070	5	3	9 x 27	2	183	90	255	43	43	615	36,3	7
500101000300070	10	3	10 x 30 *	3	195	95	355	44	47	810	64,1	7

Blueprint

