

## Closed Wedge Socket CWS

### Product information

Intended for attaching of wire rope where switching often occur, e.g. blocks of mobilecranes, or to be able to adjust the length of the wire rope. See recommended assembly to get correct results. The wedge socket is delivered complete.

**Marking house and wedge:** Wire  $\varnothing$  mm.



| Код товара   | Код     | Rope Ø range<br>mm | MBL | Finish     | Finish | A<br>mm | B<br>mm | C<br>mm | K<br>mm | TA<br>mm | TL<br>mm | Bec<br>kg | Delivery time |
|--------------|---------|--------------------|-----|------------|--------|---------|---------|---------|---------|----------|----------|-----------|---------------|
| 121501900172 | CWS 303 | 18-19              | 40  | Galvanized | G      | 220     | 100     | 34      | 40      | 90       | 254      | 7         | 7             |
| 121502200172 | CWS 304 | 20-22              | 55  | Galvanized | G      | 225     | 225     | 42      | 47      | 110      | 267      | 9         | 7             |
| 121502600172 | CWS 305 | 24-26              | 75  | Galvanized | G      | 290     | 130     | 50      | 55      | 125      | 340      | 14        | 7             |
| 121502900172 | CWS 306 | 27-29              | 90  | Galvanized | G      | 325     | 145     | 60      | 70      | 152      | 385      | 22        | 7             |
| 121503200172 | CWS 307 | 30-32              | 110 | Galvanized | G      | 360     | 160     | 68      | 75      | 165      | 428      | 30        | 7             |
| 121503600172 | CWS 308 | 34-36              | 125 | Galvanized | G      | 400     | 180     | 68      | 75      | 165      | 468      | 38        | 7             |
| 121503900172 | CWS 309 | 37-39              | 150 | Galvanized | G      | 500     | 240     | 72      | 80      | 185      | 572      | 49        | 7             |
| 121504200172 | CWS 310 | 40-42              | 170 | Galvanized | G      | 600     | 310     | 80      | 90      | 210      | 680      | 65        | 7             |
| 121504800172 | CWS 311 | 43-48              | 225 | Galvanized | G      | 640     | 325     | 90      | 100     | 225      | 730      | 100       | 7             |
| 121505200172 | CWS 312 | 49-52              | 280 | Galvanized | G      | 720     | 375     | 100     | 110     | 245      | 820      | 150       | 7             |
| 121505800172 | CWS 313 | 54-58              | 360 | Galvanized | G      | 775     | 400     | 110     | 120     | 265      | 885      | 175       | 7             |
| 121506400172 | CWS 314 | 61-64              | 425 | Galvanized | G      | 900     | 470     | 120     | 130     | 290      | 1 020    | 230       | 7             |
| 121507600172 | CWS 315 | 72-76              | 460 | Galvanized | G      | 1 000   | 500     | 130     | 150     | 330      | 1 130    | 300       | 7             |
| 121508600172 | CWS 316 | 81-86              | 625 | Galvanized | G      | 1 125   | 550     | 135     | 165     | 360      | 1 260    | 425       | 7             |

## Blueprint

